



东莞市常友实业有限公司

<http://www.bevenbi.com> info@bevenbi.com

Bevenbi

TEL:0769-82815408 82815418 FAX:83523308

Bevenbi

MKPA-S Series

BEVENBI Silver Film High-frequency HiFi Audio Capacitor

MKPA-S Series (Axial, high-purity (4N) copper wire)

Bevenbi The MKPA-S series Silver Film Capacitor are made of high-density polypropylene substrate, vacuum dust-free silver evaporation, and vacuum heat treatment. The two ends of the product electrodes are connected with quaternary high conductivity materials to ensure low loss during operation. Finally sealed with insulating epoxy resin with a flame retardant rating of 94V-0. The wires are led out with high-purity (4N) copper wire, and the appearance is stylish and dignified.

Bevenbi The MKPA-S series is one of the new products developed in recent years together with renowned acoustic experts. It is a high-end capacitor with extremely low internal power consumption and minimal leakage. When used in HiFi audio systems, it delivers exceptionally clear and detailed high-frequency response. It is the best choice for users seeking high-quality sound at a competitive price.

Bevenbi MKPA-S series Suitable for: High-end amplifiers, crossovers, HiFi audio systems, high-fidelity tube amplifiers.
The body is coated with white tape and sealed blue epoxy resin each side, with black printed lettering (non-flaking and non-deforming).



1) Technical Datas

Tol: $\pm 1\%(F)$ 、 $\pm 3\%(H)$ 、 $\pm 5\%(J)$

D.F: $(\tan \delta)$: Max. 0.0006(0.06%) For "MKPA-S" AT 1000Hz

Working Temperature: - 40 °C TO +100°C

I.R.: $C \leq 0.33\mu F$, $I.R. \geq 10000$ Mega-Ohm (AT 25 °C, 1min)

$C > 0.33\mu F$, $I.R. \geq 8000$ Mega-Ohm (AT 25 °C, 1min)

LifeTest: Operating voltage not less than 160% of the rated operating voltage at 85°C / 1,000 hours.

Humidity test.: Max. 5% D.F. Max 2% I.R. Min. 7,000 Mega-ohm Under R.H. 95% @ 40°C 1,000 Hours

Wire bending test: The wire should not break after being bent back and forth twice at 90°.

Tension test: 25°C, 1.5Kgs/30 minutes.

-----好用不贵，品质常友！-----



东莞市常友实业有限公司

<http://www.bevenbi.com> info@bevenbi.com

Bevenbi

TEL:0769-82815408 82815418 FAX:83523308

Bevenbi

MKPA-S Series

2) Dimensions(mm)

Value (uF)	100V		250V		400V		630V	
	W*OD	d	W*OD	d	W*OD	d	W*OD	d
0.1	18.5*7	0.6	18.5*7	0.6	18.5*7	0.6	18.5*7.5	0.6
0.22	18.5*8.5	0.6	18.5*8.5	0.6	18.5*8.5	0.6	18.5*10.5	0.8
0.33	18.5*10	0.8	18.5*10	0.8	18.5*10	0.8	25*10.5	0.8
0.47	18.5*10	0.8	18.5*10	0.8	18.5*11.5	0.8	25*12.5	0.8
0.56	18.5*10.5	0.8	18.5*10.5	0.8	25*10.5	0.8	25*13.5	0.8
0.68	18.5*11.5	0.8	18.5*11.5	0.8	25*11	0.8	25*14	0.8
0.82	25*10	0.8	25*10		25*11.5	0.8	25*15	0.8
1.0	25*11	0.8	25*11		25*13	0.8	31*14.5	0.8
1.2	25*10	0.8	25*12		25*14	0.8	31*16	0.8
1.5	25*10.5	0.8	25*13		25*15	0.8	31*17	0.8
1.8	25*11.5	0.8	25*14.5		31*14.5	0.8	31*19.5	0.8
2.0	25*12	0.8	25*15		31*15	0.8	35*19	0.8
2.2	25*12.5	0.8	25*16		31*16	0.8	35*19.5	0.8
2.5	25*13	0.8	31*14.5		31*17	0.8	35*21	1.0
2.7	31*12	0.8	31*15		31*17.5	0.8	35*21.5	1.0
3.0	31*12.5	0.8	31*15.5		31*18.5	0.8	35*23	1.0
3.3	31*13	0.8	31*16		31*19.5	0.8	35*23.5	1.0
3.9	31*14	0.8	31*17.5		35*19.5	0.8	45*22	1.0
4.7	31*15.5	0.8	31*19		35*21	1.0	45*24	1.0
5.6	31*17	0.8	35*19		45*20	1.0	45*26	1.0
6.8	31*18.5	0.8	35*21		45*22	1.0	45*29	1.0
8.2	31*20	0.8	45*20		45*24	1.0	55*28	1.0
10.0	35*20	1.0	45*22		45*26	1.0	55*31	1.0
12.0	35*22	1.0	45*24		45*28.5	1.0	55*33.5	1.0
15.0	45*21	1.0	45*26.5		55*28	1.0	55*37.5	1.0
18.0	45*23.5	1.0	45*29		55*31	1.0	57*41	1.2
20.0	45*24.5	1.0	55*27		55*32.5	1.0	57*43	1.2
22.0	45*25.5	1.0	55*28		55*34	1.0	57*45	1.2
27.0	45*28	1.0	55*31		55*37.5	1.0		
33.0	45*31	1.0	55*34.5		65*37.5	1.0		
47.0	55*32.5	1.0	57*41.5		67*44.5	1.2		
56.0	55*35.5	1.0	67*41		67*48.5	1.2		
68.0	55*39	1.0	67*44.5		85*48	1.2		
82.0	57*42.5	1.2	85*43.5		85*52	1.2		
100.0	57*47	1.2	85*48		85*58	1.2		

Support Special specs, inquire us for further confirmation

Sizes for capacitor body part (Unit: mm)

Tol: L +1.5/-1 mm , D<20mm ± 1 mm , D20~40mm ± 1.5 mm , D>40mm ± 2 mm

-----好用不贵，品质常友！-----